Louisiana Department of Transportation and Development
Materials & Testing Section

COARSE AGGREGATE FOR SOURCE APPROVAL

REMARKS 2

	TEST RESULTS (Max. of 15 Characters)	P/F
TYPE		XXX
ABSORPTION, % (AASHTO T 85)		
SPECIFIC GRAVITY, SSD (AASHTO T 85)		
SPECIFIC GRAVITY, APPARENT (AASHTO T 85 or TR 300)		
SPECIFIC GRAVITY, BULK (AASHTO T 85)		
ABRASION LOSS, % (AASHTO T 96)		
SOUNDNESS LOSS, % (AASHTO T 104)		
DRY UNIT MASS, LOOSE, kg/m³ (AASHTO T 19)		
DRY UNIT MASS, RODDED, kg/m³ (AASHTO T 19)		
FRICTION RATING (SPEC. 1003.06)		
LIQUID LIMIT (TR 428)		
PLASTICITY INDEX (TR 428)		
FOREIGN MATTER, % (TR 109)		
GLASSY PARTICLES, % (TR 119)		
FLAT & ELONG. PARTICLES, % (TR 119)		
CLAY LUMPS, % (TR 119)		
CLAY LUMPS & FRIABLE PARTICLES, % (TR 119)		
IRON ORE, % (TR 119)		
COAL & LIGNITE, % (TR 119)		
WOOD, % (TR 119)		
TOTAL DELETERIOUS MATERIALS, % (TR 119)		
ALKALI REACTIVITY (ASTM C 33)	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
APPROVED FOR BASE AND SURFACE COURSE		
APPROVED FOR ASPHALTIC SURF. TREATMENT		
APPROVED FOR ASPHALTIC CONCRETE		
APPROVED FOR PORTLAND CEMENT CONCRETE		
MAX. 0.6% ALKALINITY RESTRICTION		
BRIDGE DECKS EXCLUDED		
APPROVED FOR RIP RAP & STONE REVETMENT		

Tested by: _____ Date: _____ Checked by: _____ Date: _____

APPROVED BY: _____ Date: _____

09/ _____ /502/ 22- _____ /N