

State of Louisiana
Department of Transportation and Development (DOTD)
Materials and Testing Section Approved Materials Procedure
for

**HOT Poured RUBBERIZED ASPHALT TYPE JOINT SEALANT
AND BACKER ROD**

MATERIAL SPECIFICATION REFERENCE:

DOTD Standard Specifications, Subsection 1005.02.1, Supplemental Specifications and Special Provisions.

APPROVED MATERIAL EVALUATION SUBMITTAL:

The manufacturer shall submit a completed Approved Materials Evaluation Submittal to the DOTD Materials and Testing Section Coordinator listed below.

PRELIMINARY REQUIREMENTS:

The complete submittal must include:

- Complete Approved Materials Evaluation Form
- Letter requesting evaluation of the material
- Product Data Sheets
- Safety Data Sheet (SDS)
- Manufacturer's specifications
- Mixing Instructions
- Recommended application procedure and rate
- Independent Laboratory Test Results
- AASHTO National Transportation Products Evaluation Program (NTPEP) Results

The address of the contact affiliated with AASHTO NTPEP is:

NTPEP Coordinator
AASHTO National Transportation Products Evaluation Program
444 N. Capitol St. N.W.
Suite 249
Washington, D.C. 20001
Phone: (202) 624-3695
Fax: (202) 624-5806
<http://data.ntpep.org>

For detailed information, refer to the Operational Procedures of the AASHTO NTPEP available from the NTPEP Coordinator.

NOTE: Evaluation will not begin until all required items listed above are received by the Materials Laboratory.

PRELIMINARY REQUIREMENTS CONTINUED:

Certification and/or Test Reports

Submit a Certificate of Analysis reporting actual test results of the material properties for each joint sealant submitted.

TEST REQUIREMENTS:

AASHTO NTPEP

Prior to submitting an “Approved Materials Evaluation Form” to the Materials and Testing Section, the manufacturer shall have successfully completed the requirements of the AASHTO NTPEP for Hot Poured Rubberized Asphaltic Joint Sealant. The laboratory results obtained from the AASHTO NTPEP report will be used to determine conformance of the material to DOTD Standard Specifications. Laboratory and field results obtained by the AASHTO NTPEP will be used in the evaluation of this material.

Evaluation Time (2 months)

GENERAL:

Upon completion of the evaluation, the submitter will be notified in writing concerning the results of the evaluation and whether the material will or will not be added to the AML. The DOTD Materials and Testing Section Coordinator shall be notified in writing of any change from the original material submittal. The Department reserves the right to re-evaluate any material or individual material at any time. A Certificate of Analysis of the material shall be submitted annually to the DOTD Materials and Testing Section Coordinator to remain on the AML.

It is also the manufacturer’s responsibility to supply the contact information of the representative responsible for the material to the Materials Section Coordinator to remain on the AML. This is done by completing the Approved Materials Evaluation Form every two years or when there is a change in the manufacturing representative responsible for the material.

PROJECT ACCEPTANCE REQUIREMENTS:

The inclusion of any material/system/product on the AML is not blanket approval for its use. All products, regardless of prior approval, shall be sampled in accordance to the Materials Sampling Manual.

DISQUALIFICATION AND REMOVAL:

Any material may be removed from the AML at any time. Causes for removal from the AML may include, but are not limited to the following:

- Non-conformance with specifications
- Performance requirements
- Failure to notify the Department of any change in material formulation.
- Failure of the supplier to provide proper certifications as required by this procedure
- Failing test results obtained by the Materials Section of project verification samples.
- Failure to supply current contact information for the material representative in accordance with this procedure.

REQUALIFICATION:

Any product which has been disqualified and/or removed from the AML will be considered for re-evaluation only after submission of a formal request along with acceptable evidence that the problems causing the disqualification and/or removal have been resolved.

DOTD MATERIALS AND TESTING SECTION COORDINATOR:

Paul Garneau, E.I.
Special Testing Engineer Intern
DOTD Materials and Testing Section
5080 Florida Blvd.
Baton Rouge, LA 70806-4132
(225) 248-4102
Paul.Garneau@la.gov

Approved 05/24/17



BRIAN OWENS, P.E.
DOTD MATERIALS ENGINEER ADMINISTRATOR