

NOTES

FOR ADDITIONAL INFORMATION ON GUARD RAIL, SEE STD. PLAN GR-200 & GR-202.

ALL WORK AND MATERIALS REQ'D. TO INSTALL GUARD RAIL ON THIS TYPE STRUCTURE SHALL BE PAID FOR UNDER ITEM 704-01-01020 GUARD RAIL (SINGLE THRIE BEAM).


ALTHOUGH ITEM 704-01-01020 CALLS FOR 6'-3" POST SPACING, THE NEW POST ON THIS TYPE STRUCTURE SHALL BE PLACED IN THE SAME LOCATION AS THE EXISTING ONES.

GUARD RAIL SPLICES SHALL BE MADE AT POST LOCATIONS ONLY.

USE 7/8" MECHANICAL SYSTEM AS LISTED ON APPROVED MATERIALS LIST, PRODUCT CATEGORY "CONCRETE ANCHOR SYSTEMS."

ALL STRUCTURAL STEEL SHALL BE ASTM A-36 AND GALVANIZED. ALL 5/8" Ø BOLTS SHALL BE ASTM A307.

FOR INFORMATIONAL PURPOSES ONLY



Paul B. Fossier, Jr.
6-31-17

SHEET NUMBER	
DESIGNED	P. FOSSIER
CHECKED	C. GAUDRY
PARISH	
CONTROL SECTION	
STATE	
PROJECT	
DESIGNED	P. FOSSIER
CHECKED	C. GAUDRY
PARISH	
CONTROL SECTION	
STATE	
PROJECT	
NO.	4-8-16
DATE	
REVISION OR CHANGE ORDER DESCRIPTION	GUARDRAIL HEIGHT, ANCHOR BOLT NOTE AND BASE PLATE
BY	P. F.
SIDE MOUNTED GUARD RAIL FOR BRIDGES	
BD.2.6.4.2.10	
BRIDGE AND STRUCTURAL DESIGN	