


POURED SILICONE JOINT - SECTION
(N.T.S.)

FOR INFORMATIONAL PURPOSES ONLY

NOTES:

1. JOINT FABRICATION AND CONSTRUCTION SHALL BE IN ACCORDANCE WITH SECTION 815 OF THE DOTD STANDARD SPECIFICATIONS.
2. THE MANUFACTURER'S RECOMMENDED CONSTRUCTION METHODS SHALL BE FOLLOWED.
3. PREFORMED JOINT FILLER SHALL CONFORM TO SECTION 1005.01 OF THE STANDARD SPECIFICATION.
4. POURED SILICONE JOINT SEALANT AND BACKER MATERIAL SHALL CONFORM TO SECTION 1005.02.3 OR 1005.02.4 OF THE STANDARD SPECIFICATIONS. THE BACKER MATERIAL SHALL BE COMPRESSED TO 80% OR LESS OF ITS ORIGINAL DIAMETER FOR INSTALLATION.
- Δ 5. SEE THE JOINT DATA TABLE IN PLANS FOR DESIGN AND INSTALLATION REQUIREMENTS.
6. JOINT SHALL BE PAID FOR UNDER PAY ITEM JOINT SEAL (POURED).



SHEET NUMBER	
DESIGNED A. LANCASTER	PARISH
CHECKED K. KEMP	CONTROL SECTION
DETAILER J. W. P.	STATE
CHECKED K. KEMP	PROJECT
REVIEWED Z. Z. FU	
SERIES # 1 OF 1	
NO.	DATE
REVISION OR CHANGE ORDER DESCRIPTION	
BY	
MISC. SPAN DETAILS	
POURED SILICONE JOINT	
MISC. SPAN DETAILS (JOINTS)	
BD.2.4.5.3.01	
DOTD DOTD BRIDGE DESIGN	