



NOTES:

FOR ADDITIONAL INFORMATION ON GUARD RAIL, SEE STD. PLAN GR-200.

ALL WORK AND MATERIALS REQ'D. TO INSTALL GUARD RAIL ON THE STRUCTURE SHALL BE PAID FOR UNDER ITEM 704-01-01020

ANY DAMAGE DONE TO THE STRUCTURE DURING CONSTRUCTION NOT RELATED TO THE WORK REQUIRED SHALL BE REPAIRED AT THE CONTRACTORS EXPENSE AND TO THE SATISFACTION OF THE PROJECT ENGINEER.

ALL HOLES (VERTICAL OR HORIZONTAL) DRILLED INTO AN EXISTING CONCRETE STRUCTURE SHALL BE CLEANED WITH COMPRESSED AIR AND MADE FREE OF ANY OIL OR RESIDUE. HOLES SHALL BE FILLED WITH INJECTION SYSTEM AS LISTED ON QPL 40. PLACE ROD IN HOLE IMMEDIATELY AND WAIT FOR THE MANUFACTURERS CURE TIME.

NOMINAL POST SPACING ON THIS SPAN IS 8'-9" (ORIGINAL DESIGN). NEW POST ARE REQUIRED AND SHALL BE INSTALLED AS SHOWN. GUARD RAIL SPLICES SHALL BE MADE AT POST LOCATIONS ONLY.

THE POST LOCATED ON THE FLARED BRIDGE END SHALL BE INSTALLED AS SHOWN. IF A FLARED END DOES NOT EXIST A NORMAL 6" X 8" TIMBER POST OR A APPROVED ALTERNATE SHALL BE USED.

* NOTE: (AT END SPAN POST LOCATION ONLY) THE INTERIOR BOLT SHALL BE AS SHOWN. THE OUTER BOLT NEARER TO END JOINT) SHALL BE DRILLED IN THE SAME MANNER AS THE FRONT ANCHOR BOLTS. ALL STRUCTURAL STEEL SHALL BE ASTM A36 AND GALVANIZED.

☐ THE EXISTING POST SHALL BE REMOVED AND NEW POST BE MOUNTED ON THE TOP OF THE STRUCTURE AS SHOWN AND AT THE SAME SPACING.

● 6" X 8" X 1'-10 1/2" TIMBER BLOCK

* 1/2" Ø HOLES FOR 1" Ø H.S. BOLTS ASTM A449 W/HEX NUT AND 2 WASHERS

ALL 5/8" Ø BOLTS SHALL BE ASTM A307.



Paul B. Fossier, Jr.
4/9/09

BRIDGE AND STRUCTURAL DESIGN		BRIDGE RAIL REHABILITATION (WASKEY BRIDGES)			DESIGNED		PARISH		SHEET NUMBER
		CHECKED			FEDERAL PROJECT				
		DATE	12-2008		STATE PROJECT				
		BY							
STANDARD DETAIL		NO.	DATE	REVISION DESCRIPTION					
					J. BENTON P. FOSSIER				